

Product Information Sheet

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

Supplier's name or trade mark: di-soric

Supplier's address: Environmental, Gielster Stück 2, 58513 Lüdenscheid, DE

Model identifier: MB-R-715-B5 / 213806

Type of light source:

Lighting technology used:	LED	Non-directional or directional:	DLS
Light source cap-type (or other electric interface)	offene Kabelenden		
Mains or non-mains:	NMLS	Connected light source (CLS):	No
Colour-tuneable light source:	No	Envelope:	-
High luminance light source:	No		
Anti-glare shield:	No	Dimmable:	No


Product parameters

Parameter	Value	Parameter	Value
General product parameters:			
Energy consumption in on-mode (kWh/1000 h), rounded up to the nearest integer	24	Energy efficiency class	G
Useful luminous flux (ϕ_{use}), indicating if it refers to the flux in a sphere (360°), in a wide cone (120°) or in a narrow cone (90°)	1 560 in Wide cone (120°)	Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set	5 000
On-mode power (P_{on}), expressed in W	24,0	Standby power (P_{sb}), expressed in W and rounded to the second decimal	0,00
Networked standby power (P_{net}) for CLS, expressed in W and rounded to the second decimal	-	Colour rendering index, rounded to the nearest integer, or the range of CRI-values that can be set	80
Outer dimensions without separate control gear, lighting control	Height	37	Spectral power distribution in the range 250 nm to 800 nm, at full-load
	Width	760	
	Depth	46	
			See image in last page


parts and non-lighting control parts, if any (millimetre)			
Claim of equivalent power ^(a)	-	If yes, equivalent power (W)	-
		Chromaticity coordinates (x and y)	0,430 0,400
Parameters for directional light sources:			
Peak luminous intensity (cd)	596	Beam angle in degrees, or the range of beam angles that can be set	106
Parameters for LED and OLED light sources:			
R9 colour rendering index value	10	Survival factor	1,00
the lumen maintenance factor	0,98		

(a): not applicable;

(b): not applicable;



Model placed on the Union market from 27/10/2022



EPREL registration number: 1853628

<https://eprel.ec.europa.eu/qr/1853628>

Supplier: di-soric GmbH & Co. KG (Manufacturer)

Website: <https://www.di-soric.com>

Customer care service:

Name: Environmental

Website: www.di-soric.com

Email: info@di-soric.com

Phone: +49 (0) 2351 / 9844-402

Address:

Gielster Stück 2
58513 Lüdenscheid
Germany