




203486
OGUTI 005 G3K-TSSL
Optical label sensor

- Fast, simple, safe: Sensitivity adjustment via teach key
- Auto-teach during a running process
- LED indicator for the teach procedure
- Detection of an extremely wide range of different labels
- Large functional reserve
- Light/dark switching



Function										

Technical data (typ.)	+20°C, 24 V DC
Service voltage	10 ... 35 V DC (Supply Class 2)
No-load current (max.)	35 mA
Insulation voltage endurance	500 V
Leg length internal	40 mm
Housing dimensions	37.5 x 60 x 15 mm
Housing length	60 mm
Housing height	37.5 mm
Housing width	15 mm
Housing material	Die-cast zinc (Black, painted)
Protection class	III, operation on protective low voltage
Approvals	UL
Operating principle	Optical
Evaluation	digital
Design	Fork
Product series	OGUTI Optical
Switching output	Push-pull, 200 mA, NO/NC, switchable
Voltage drop (max.)	2 V
Light source	LED
Color	Infrared
Wavelength	880 nm
Modulation	Clocked
Ambient light immunity	40 kLx
Fork opening	5 mm
Resolution	Ø 0.5 mm
Switching hysteresis (max.)	0.1 mm



203486
OGUTI 005 G3K-TSSL
Optical label sensor

Technical data (typ.)	+20°C, 24 V DC
Reproducibility	< 0.03 mm
Sensitivity adjustment	Teach button
Switching frequency	3000 Hz
Ambient temperature during operation	-10 ... +60 °C
Protection type	IP 67
Connection	Connector, M8, 3-pin
Connection cable	TK ...
More information / accessories	https://www.di-soric.com/203486