




**205319**  
**DCR 40 K 02 NSLK**  
**Inductive proximity sensor**

- Highly flexible cable
- Integrated amplifier
- Short-circuit protection
- Starting pulse suppression
- LED



Function													

Technical data (typ.)	+20°C, 24 V DC
Service voltage	10 ... 35 V DC
Internal power consumption	< 10 mA
Insulation voltage endurance	500 V
Installation type	Flush
Housing dimensions	40 x 12 mm
Housing length	26 mm
Housing height	40 mm
Housing width	12 mm
Housing material	Plastic
Material of cable	Polyurethane
Protection class	III, operation on protective low voltage
Operating principle	inductive
Evaluation	digital
Design	Cuboid design
Product series	INE Extended
Switching output	npn, 200 mA, NO
Voltage drop (max.)	2.4 V
Switching distance (SN)	2 mm
Standardized measuring plate	12 x 12 x 1 mm
Switching hysteresis (max.)	15 %
LED Anzeige	Yes
Switching frequency	1000 Hz
Ambient temperature during operation	-30 ... +70 °C
Protection type	IP 67
Connection	Cable, 2.0 m (flying leads)



**205319**

**DCR 40 K 02 NSLK**

**Inductive proximity sensor**

[More information / accessories](#)

<https://www.di-soric.com/205319>