




206563
LVX-O16
Evaluation electronics

- Evaluation electronics for two light grids LI ...
- Diagnosis LEDs
- Freely configurable functions
- DIN-rail mountable



- 1) LED status inputs/outputs, mode In/Out (green)
 2) Transmitter 1
 3) Transmitter 2
 4) Receiver 1
 5) Receiver 2
 6) LED SUPPLY (green)

Function									
									CE
									

Technical data (typ.)	+20°C, 24 V DC
Service voltage	20 ... 26 V DC
Assembly	DIN-rail mountable
Quantity	2 (number of Light curtains to be operated)
Housing material	Plastic
Protection class	III, operation on protective low voltage
EMC directives	EN 61000-6-3:2001 / EN 61000-6-1:2001
Number of inputs/outputs	3
Output function	configurable
Switching output	19x
Switching capacity	< 7 W
Interface	<ul style="list-style-type: none"> ■ Combined IOs (3x) ■ RS232 ■ CANopen
Inputs for which parameters can be set	24 V DC, 12 mA, 3,000 Hz (1x)
Beam evaluation	Parameters can be configured horizontally / diagonally
Number of beams	500 (Max. evaluable)
Display	LED (Error indicator)
Cycle time per light beam	0.05 ms (abhängig von Konfiguration und Reichweite der Lichtgitterleisten)

**206563****LVX-O16****Evaluation electronics****Technical data (typ.)****+20°C, 24 V DC**

Ambient temperature during operation

0 ... +40 °C

Protection type

IP 00

Connection

Connection compartment

More information / accessories<https://www.di-soric.com/206563>