




208176
BEK-A100-G3T-K-BS
Barlight

- Extremely high illuminance due to the most modern high-power LEDs
- Integrated power control with high efficiency
- Intelligent temperature control with switch-off automatic
- Homogeneous light field thanks to special LED optics
- High protection type
- Separate inputs for trigger signal and trigger polarity
- Robust metal housing
- Universal mounting options
- Scratch-resistant safety screen
- Crossbars and attachment optics available as an option



Function									

Technical data (typ.)	+20°C, 24 V DC
Service voltage	18 ... 30 V DC (Supply Class 2)
Internal power consumption	620 mA (24 V DC)
Power	14.5 W (24 V DC)
Inverse polarity protection	Yes
Illuminated area	96 x 23 mm
Housing dimensions	40 x 60 x 113 mm
Housing material	Aluminum (Black, Anodized)
Material	PMMA, hardcoated (Safety screen)
Weight	470 g
Protection class	III, operation on protective low voltage
Risk group (DIN EN 62471)	Risk group 2
Approvals	UL
Design	Barlight
Trigger input high level	3.3 ... 30.0 V
Trigger input low level	< 2.8 V
Light source	LED
Color	Blue
Wavelength	470 nm
Deflection angle FWHM	30°



208176
BEK-A100-G3T-K-BS
Barlight

Technical data (typ.)	+20°C, 24 V DC
Light intensity	<ul style="list-style-type: none"> ■ 49.0 kLx (100.0 mm) ■ 22.0 kLx (200.0 mm) ■ 5.00 kLx (500.0 mm)
Control	Integrated power control
Display	LED Green - Operating display
Shock/vibration load	30 g, 11 ms / 10 ... 55 Hz, 1.0 mm
Ambient temperature during operation	0 ... +40 °C
Protection type	IP 67
Connection	Pigtail, 0.3 m (+ Connector M12), 4-pin
Connection cable	VK ...
More information / accessories	https://www.di-soric.com/208176