




209700
BE-F30/30RL-G5-K-BS
Area light

- High light intensity
- A minimal edge region
- Homogeneous luminous field
- Very compact design
- High protection type IP 67
- Robust design



Function										

Technical data (typ.)	+20°C, 24 V DC
Service voltage	24 V DC (Supply Class 2)
No-load current (max.)	46 mA (24 V DC)
Power	1.1 W (24 V DC)
Inverse polarity protection	no
Illuminated area	30 x 30 mm
Housing dimensions	30 x 30 x 20 mm
Housing material	Aluminum (Black, Anodized)
Material	PMMA, diffuse (Protection optics)
Weight	45 g
Protection class	III, operation on protective low voltage
Risk group (DIN EN 62471)	Free group
Approvals	UL
Design	Area light
Light source	LED
Color	White
Wavelength	5000 K
Deflection angle FWHM	120°
Control	Integrated power control
Shock/vibration load	30 g, 11 ms / 10 ... 55 Hz, 1.0 mm
Ambient temperature during operation	0 ... +40 °C (Continuous operation)
Protection type	IP 67



209700
BE-F30/30RL-G5-K-BS
Area light

Technical data (typ.)

+20°C, 24 V DC

Connection

Pigtail, 0.3 m, M12, 3-pin

Connection cable

VK ...

More information / accessories

<https://www.di-soric.com/209700>