







213332
IOL-Portable
IOL Portable

- Universal IO-Link handheld master
- App-based, no prior knowledge necessary
- Integrated touchscreen and plug connectors
- Integrated battery, IO-Link master and WLAN
- For identification, configuration and diagnostics
- IODD download via IODDfinder
- For devices with IODD Specification 1.1



Function											
											  
Technical data (typ.)					+20°C, 24 V DC						
Power consumption	80 mA										
Inverse polarity protection	Yes										
Power supply	24V / 80 mA (IO-Link Device from battery)										
Housing dimensions	62 x 222 x 90 mm										
Housing material	Polycarbonate										
Protection class	III, operation on protective low voltage										
To be used for	For devices with IODD Specification 1.1										
Scope of delivery	IO-Link Hand Held Master, cable with clamps 0,3 m with connector M12, 4-wires, Protection bag, Micro-USB-cable, Quick-start-guide										
Functions	Without computer										
Communication	IO-Link specification V 1.1, IO-Link port class A										
Ambient temperature during operation	0 ... +40 °C										
Protection type	IP 30										
Connection	Socket, M8, 3-pin										
Connection 2	Socket, M8, 4-pin										
Connection 3	Socket, M12, 4-pin										
More information / accessories					https://www.di-soric.com/213332						