







213332
IOL-Portable
IOL Portable

- Universal IO-Link handheld master
- App-based, no prior knowledge necessary
- Integrated touchscreen and plug connectors
- Integrated battery, IO-Link master and WLAN
- For identification, configuration and diagnostics
- IODD download via IODDfinder
- For devices with IODD Specification 1.1



Function												
												  
Technical data (typ.)						+20°C, 24 V DC						
Power consumption	80 mA											
Inverse polarity protection	Yes											
Power supply	24V / 80 mA (IO-Link Device from battery)											
Housing dimensions	62 x 222 x 90 mm											
Housing material	Polycarbonate											
Protection class	III, operation on protective low voltage											
To be used for	For devices with IODD Specification 1.1											
Scope of delivery	IO-Link Hand Held Master, cable with clamps 0,3 m with connector M12, 4-wires, Protection bag, Micro-USB-cable, Quick-start-guide											
Functions	Without computer											
Communication	IO-Link specification V 1.1, IO-Link port class A											
Ambient temperature during operation	0 ... +40 °C											
Protection type	IP 30											
Connection	Socket, M8, 3-pin											
Connection 2	Socket, M8, 4-pin											
Connection 3	Socket, M12, 4-pin											
More information / accessories						https://www.di-soric.com/213332						