



**213752**  
**SBT-RGB-R50-3S-B5**  
**Signal column**

- Status display 360°
- Strong signal effect thanks to state-of-the art, high-efficiency LEDs
- Low energy consumption
- Can be used immediately thanks to three trigger inputs (eight predefined/user-defined color settings)
- Freely configurable functions via IO-Link (process data)
- Simple installation (M30 threading)



**Legende / Legend:**

>RT< = Rot langsam blinkend / flashing red slowly  
 >>RT<< = Rot blitzend / rapidly flashing red  
 >BUZ< = Buzzer intermittierend / Buzzer intermittent (1Hz)  
 >>BUZ<< = Buzzer intermittierend / Buzzer intermittent (2,5Hz)

All Trigger Inputs have a delay ~50 ms.  
 Pre-sets can be defined via IO-Link.

TRIG 1	TRIG 2	TRIG 3	Pre-Set	Factory setting (Seg 1 / Seg 2 / Seg 3 / BUZ)			
				Var. 3S		Var. 3B	
0	0	0	1	--	--	--	--
1	0	0	2	--	--	RT	RT
0	1	0	3	GN	--	GN	--
1	1	0	4	--	YE	--	YE
0	0	1	5	BU	--	BU	--
1	0	1	6	WH	--	WH	--
0	1	1	7	--	--	>RT<	>BUZ<
1	1	1	8	--	--	>>RT<<	>>BUZ<<

BK: black  
BN: brown
BU: blue  
GN: green
GY: grey  
WH: white
YE: yellow

Function										

Technical data (typ.)	+20°C, 24 V DC
Service voltage	18 ... 30 V DC (Supply Class 2)
Internal power consumption	175 mA (24 V DC)
Power	4.2 W (24 V)
Inverse polarity protection	Yes
Illuminated area	50 x 37 mm (Ø x H / segment)
Dimensions of luminaire unit (Ø x H)	Ø 50.6 x 165 mm
Number of segments	3
Housing material	Aluminum (natural, Anodized)
Material	Polycarbonate (Diffusor)
Weight	270 g
Protection class	III
Approvals	UL
Model	Signal column
Operating modes	External trigger / segment mode / level mode / demo mode, LED operating modes: Static / Blinking / Flashing
Buzzer	Without buzzer
Color selection	Red, green, yellow, blue, white, orange, pink, user-defined
Light intensity can be adjusted	10 to 100 %, via IO-Link
Trigger input high level	> 8.0 V



**213752**  
**SBT-RGB-R50-3S-B5**  
**Signal column**

<b>Technical data (typ.)</b>	<b>+20°C, 24 V DC</b>
Trigger input low level	< 5.0 V
Trigger input	8 color presets: selectable via trigger 1 + 2 +3
Interface	<ul style="list-style-type: none"><li>■ IO-Link (V1.1, COM2 38,4 kBd, 5000 µs)</li><li>■ for parameterization (process data)</li></ul>
Color	RGB
Vibration load	10 ... 55 Hz / 0.35 mm
Ambient temperature during operation	0 ... +50 °C
Protection type	IP 65
Connection	Connector, M12, 5-pin
Connection cable	VK ... /5-SB
<b>More information / accessories</b>	<b><a href="https://www.di-soric.com/213752">https://www.di-soric.com/213752</a></b>