



206503
LA 40-50-1950-2160 I-D
Light grids

- Horizontal beam evaluation
- Integrated evaluation electronics
- Switching output
- Fault alarm output
- Compact design
- Aluminum housing
- Easy to install



Function													
												CE	

Technical data (typ.)	+20°C, 24 V DC
Service voltage	20.4 ... 28.8 V DC
Power consumption	8 W
Assembly	Threaded bolt (5)
Profile cross section	12 x 24 mm
Dimension	<ul style="list-style-type: none"> ■ A: 130 mm ■ B: 500 mm ■ X: 20 mm ■ Y: 185 mm
Profile length	2160 mm
Housing material	Aluminum (silver, Anodized)
Protection class	III, operation on protective low voltage
EMC directives	EN 61000-6-3:2001 / EN 61000-6-1:2001
Evaluation	horizontal
Evaluation electronics	integrated
Output function	Dark switching
Switching output	pnp, 200 mA, NO, short-circuit-proof
Light source	LED
Color	Infrared
Wavelength	880 nm

**206503****LA 40-50-1950-2160 I-D****Light grids**

Technical data (typ.)	+20°C, 24 V DC
Beam evaluation	via integrated evaluation electronics
Beam separation	50 mm
Number of beams	40
Monitoring height	1950 mm
Range	700 ... 4000 mm (factory setting)
Display	LED (Service voltage / output stage, error (alarm))
Cycle time per light beam	1 ms
Total cycle time	Anzahl Lichtstrahlen x 1 ms + 4 ms
Basic processing time	4 ms
Ambient temperature during operation	-10 ... +45 °C
Protection type	IP 54 (IP 65 optional)
Connection	Cable, 4.0 m (with ferrule)
More information / accessories	https://www.di-soric.com/206503