



**212779**  
**SB-RGB-126-K-B5**  
**Signal lighting**

- High illuminance due to state-of-the-art, highly efficient LEDs
- Easy operation is also possible without IO-Link
- Freely configurable functions via IO-Link
- Long life thanks to intelligent thermal management
- Large light field for optimal display of the machine status
- Can be used immediately thanks to three color pre-sets: red - green - yellow
- High protection type IP 67
- Magnetic holder set available as an option
- Adjustable mounting angle optionally available
- Pluggable diffusion filter optionally available



1) Illuminated area

BK: black      BU: blue  
 BN: brown      GY: grey

Pre-Sets / Factory settings		
Trigger 1	Trigger 2	Farbe / Color
Lo	Lo	aus / off
Hi	Lo	rot / red
Lo	Hi	grün / green
Hi	Hi	gelb / yellow

WH: white

Function									

Technical data (typ.)	+20°C, 24 V DC
Service voltage	24 V DC (± 5%, Supply Class 2)
Internal power consumption	115 mA / 150 mA RMS Peak (24 V DC)
Power	2.8 W (24 V DC)
Inverse polarity protection	Yes
Illuminated area	95 x 30 mm
Housing length	125 mm
Housing height	10 mm
Housing width	40 mm
Housing material	Aluminum (natural, Anodized)
Material	PU, crystal clear (Window)
Weight	115 g
Protection class	III, operation on protective low voltage
Risk group (DIN EN 62471)	Free group
Approvals	UL
Model	Signal lighting
Product series	SB-RGB
Number of segments (max)	1
Operation modes	RGB: constant, blinking, flashing
Light intensity can be adjusted	10 to 100 %, via IO-Link
Trigger input high level	> 8.0 V
Trigger input low level	< 5.0 V
Trigger input	3 color presets: selectable via trigger 1 + 2
Interface	<ul style="list-style-type: none"> <li>■ IO-Link (V1.1, COM2 38.4 kBd, 2300 µs)</li> <li>■ for parameterization (process data)</li> </ul>
Light source	LED
Color	RGB (user-defined)



**212779**

**SB-RGB-126-K-B5**

**Signal lighting**

<b>Technical data (typ.)</b>	<b>+20°C, 24 V DC</b>
Deflection angle FWHM	120°
Shock/vibration load	30 g, 11 ms / 10 ... 55 Hz, 1.0 mm
Ambient temperature during operation	0 ... +40 °C
Protection type	IP 67
Connection	Pigtail, 0.3 m, M12, 5-pin
Connection cable	VK ... /5
<b>More information / accessories</b>	<b><a href="https://www.di-soric.com/212779">https://www.di-soric.com/212779</a></b>