


213025
OTM05-50PS-2R
Retroreflective diffuse sensor

- Extremely small design
- Red light
- Scanning range preset
- Stainless steel housing
- Can be installed countersunk
- Large temperature range



Function													

Technical data (typ.)	+20°C, 24 V DC
Service voltage	10 ... 30 V DC
No-load current (max.)	15 mA
Inverse polarity protection	Yes
Thread	M5 x 0.5
Housing length	35.8 mm
Housing material	Stainless steel (V2A)
Material of cable	Polyurethane
Material	Plastic (Window / optics)
Weight	30 g
Protection class	III, operation on protective low voltage
Operating principle	Retroreflective diffuse sensor
Evaluation	digital
Design	Thread
Switching output	pnp, 100 mA, NO
Voltage drop (max.)	2 V
Light source	LED
Color	red
Wavelength	630 nm
Light spot size	18 x 20 mm (at 50 mm distance)
Scanning range	50 mm



213025

OTM05-50PS-2R

Retroreflective diffuse sensor

Technical data (typ.)

+20°C, 24 V DC

Standardized measuring plate

200 x 200 mm (white)

Sensitivity adjustment

no setting elements

Display

LED yellow - Switching output

Switching frequency

1000 Hz

Ambient temperature during operation

-25 ... +65 °C

Protection type

IP 67

Connection

Cable, 2.0 m

More information / accessories

<https://www.di-soric.com/213025>