



213753
SBT-RGB-R50-3B-B5
Signal column

- Status display 360°
- Strong signal effect thanks to state-of-the art, high-efficiency LEDs
- Low energy consumption
- Can be used immediately thanks to three trigger inputs (eight predefined/user-defined color settings)
- Freely configurable functions via IO-Link (process data)
- Simple installation (M30 threading)
- Buzzer



Legende / Legend:

>RT< = Rot langsam blinkend / flashing red slowly
 >>RT<< = Rot blitzend / rapidly flashing red
 >BUZ< = Buzzer intermittierend / Buzzer intermittent (1Hz)
 >>BUZ<< = Buzzer intermittierend / Buzzer intermittent (2,5Hz)

All Trigger Inputs have a delay ~50 ms.
 Pre-sets can be defined via IO-Link.

TRIG 1	TRIG 2	TRIG 3	Pre-Set	Factory setting (Seg 1 / Seg 2 / Seg 3 / BUZ)			
				Var. 3S		Var. 3B	
0	0	0	1	--	--	--	--
1	0	0	2	--	--	RT	RT
0	1	0	3	GN	--	GN	--
1	1	0	4	--	YE	--	YE
0	0	1	5	BU	--	BU	--
1	0	1	6	WH	--	WH	--
0	1	1	7	--	--	>RT<	>BUZ<
1	1	1	8	--	--	>>RT<<	>>BUZ<<

BK: black BU: blue GY: grey YE: yellow
 BN: brown GN: green WH: white

Function											

Technical data (typ.)	+20°C, 24 V DC
Service voltage	18 ... 30 V DC (Supply Class 2)
Internal power consumption	195 mA (24 V DC)
Power	4.7 W (24 V)
Inverse polarity protection	Yes
Illuminated area	50 x 37 mm (Ø x H / segment)
Number of segments	3
Housing material	Aluminum (natural, Anodized)
Material	Polycarbonate (Diffusor)
Weight	310 g
Protection class	III, operation on protective low voltage
Model	Signal column
Operating modes	External trigger / segment mode / level mode / demo mode, LED operating modes: Static / Blinking / Flashing
Buzzer	Yes, 80 (dB(A) typ. @ 50 cm)
Color selection	Red, green, yellow, blue, white, orange, pink, user-defined
Light intensity can be adjusted	10 to 100 %, via IO-Link
Trigger input high level	> 8.0 V
Trigger input low level	< 5.0 V
Trigger input	8 color presets: selectable via trigger 1 + 2 +3



213753
SBT-RGB-R50-3B-B5
Signal column

Technical data (typ.)	+20°C, 24 V DC
Interface	<ul style="list-style-type: none">■ IO-Link (V1.1, COM2 38,4 kBd, 5000 µs)■ for parameterization (process data)
Color	RGB
Vibration load	10 ... 55 Hz / 0.35 mm
Ambient temperature during operation	0 ... +50 °C
Protection type	IP 20
Connection	Connector, M12, 5-pin
Connection cable	VK ... /5-SB
More information / accessories	https://www.di-soric.com/213753