




205680
BE 1-A130-G2-K-BS
Barlight

- Very compact design
- Homogeneous luminous field
- Cable outlet usable at the front or back side
- Universal mounting options
- Metal casing
- Homogeneous illumination
- High efficiency
- Robust metal housing



Function												



Technical data (typ.)	+20°C, 24 V DC
Service voltage	24 V DC (Supply Class 2)
Internal power consumption	190 mA (24 V DC)
Power	4.5 W (24 V DC)
Illuminated area	130 x 16 mm
Housing dimensions	16 x 20 x 144 mm
Housing material	Aluminum (Black, Anodized)
Material	Polyurethane (Cable)
Protection class	III, operation on protective low voltage
Risk group (DIN EN 62471)	Free group
Approvals	UL
Design	Barlight
Light source	LED
Color	green
Wavelength	525 nm
Deflection angle FWHM	40°
Light intensity	<ul style="list-style-type: none"> ■ 11.6 kLx (100.0 mm) ■ 3.50 kLx (200.0 mm) ■ 6.00 kLx (500.0 mm)
Control	without power control
Ambient temperature during operation	0 ... +40 °C
Protection type	IP 20
Connection	Pigtail, 0.3 m, M12, 3-pin
Connection cable	VK ...



205680
BE 1-A130-G2-K-BS
Barlight

[More information / accessories](#)

<https://www.di-soric.com/205680>