





206445
VO-M6/50-M6x30-2.5
Focus optics

- For operating color sensors with fiber optic connection
- Robust design



Technical data (typ.)	+20°C, 24 V DC
Component	Focus optics
Operation with	WRB 120 S-SG-M6x30-2.5, WRB 120 P-SG-M6x30-2.5
For FSB 10 M G1-B8	To be used with WRB 120 S-SG-M6x30-2.5, To be used with WRB 120 P-SG-M6x30-2.5
For FSB 50 M 60 G3-B8	To be used with WRB 120 S-SG-M6x30-2.5, To be used with WRB 120 P-SG-M6x30-2.5
For FS 50 M G3-B8	To be used with WRB 120 S-SG-M6x30-2.5, To be used with WRB 120 P-SG-M6x30-2.5
For FS 12-100-1 M G3-B8	To be used with WRB 120 S-SG-M6x30-2.5, To be used with WRB 120 P-SG-M6x30-2.5
For FS 12-100-1 M G3-B8-E	To be used with WRB 120 S-SG-M6x30-2.5, To be used with WRB 120 P-SG-M6x30-2.5
For FS 12-100-2 M G3-B8	To be used with WRB 120 S-SG-M6x30-2.5, To be used with WRB 120 P-SG-M6x30-2.5
Light spot size	Ø 6 mm
Working distance	50.0 mm
Working range	35 ... 60 mm
More information / accessories	https://www.di-soric.com/206445