





**206721**  
**BE 1-A65/120-G1-K-BS**  
**Barlight**

- Very compact design
- Homogeneous luminous field
- Cable outlet usable at the front or back side
- Universal mounting options
- Metal casing
- High efficiency
- Robust metal housing



Function									

Technical data (typ.)	+20°C, 24 V DC
Service voltage	24 V DC (Supply Class 2)
Internal power consumption	80 mA (24 V DC)
Power	2.0 W (24 V DC)
Inverse polarity protection	Yes
Illuminated area	65 x 16 mm
Housing dimensions	16 x 20 x 84 mm
Housing material	Aluminum (Anodized)
Risk group (DIN EN 62471)	Free group
Approvals	UL
Design	Barlight
Light source	LED
Color	red
Wavelength	625 nm
Deflection angle FWHM	120°
Light intensity	<ul style="list-style-type: none"> <li>■ 1.50 kLx (100.0 mm)</li> <li>■ 390 Lux (200.0 mm)</li> <li>■ 65.0 Lux (500.0 mm)</li> </ul>
Control	without power control
Ambient temperature during operation	0 ... +40 °C (Continuous operation)
Protection type	IP 20
Connection	Pigtail, 0.3 m, M12, 3-pin
Connection cable	VK ...



**206721**

**BE 1-A65/120-G1-K-BS**

**Barlight**

[More information / accessories](#)

<https://www.di-soric.com/206721>