




**206809**  
**BEK-F150/150-G0TI-IBS**  
**Area light**

- Constant level of light intensity over the entire voltage range
- Homogeneous luminous field
- High efficiency
- Light intensity can be adjusted



Function										

Technical data (typ.)	+20°C, 24 V DC
Service voltage	15 ... 35 V DC (Supply Class 2)
No-load current (max.)	430 mA (24 V DC)
Power	10.3 W (24 V DC)
Inverse polarity protection	Yes
Illuminated area	150 x 150 mm
Housing dimensions	180 x 210 x 15 mm
Housing material	Aluminum (Black, Anodized)
Material	PC, opal diffuse (Protection optics)
Protection class	III, operation on protective low voltage
Risk group (DIN EN 62471)	Free group
Approvals	UL
Design	Area light
Characteristics	Trigger input
Trigger input high level	3.3 ... 35.0 V
Trigger input low level	< 2.8 V
Light source	LED
Color	Infrared
Wavelength	850 nm
Deflection angle FWHM	120°
Control	Integrated power control
Display	LED Green - Operating display
Shock/vibration load	30 g, 11 ms / 10 ... 55 Hz, 1.0 mm

**206809****BEK-F150/150-G0TI-IBS****Area light****Technical data (typ.)****+20°C, 24 V DC**

Ambient temperature during operation

0 ... +40 °C

Protection type

IP 67

Connection

Connector, M12, 3-pin

Connection cable

VK ...

**More information / accessories**<https://www.di-soric.com/206809>