



208219
BE-A300-F1-K
Barlight

- High excess current factor
- Pulse mode for "freezing" and inspecting moving objects with extremely high illuminance
- Long life thanks to intelligent thermal management
- Homogeneous luminous field
- High protection type
- Robust metal housing
- Universal mounting options
- Scratch-resistant safety screen
- Crossbars and attachment optics available as an option




Betrieb ausschließlich mit Flash-Controller an einem *Supply Class 2* - Netzteil!
Use only with flash equipment driven by a power supply *Class 2*!
A utiliser exclusivement avec un contrôleur d'impulsion connecté a une alimentation *Class 2*!

1) Mounting groove for nut 2) Illuminated area

Function										

Technical data (typ.)	+20°C
Power consumption (in pulse / max.)	720 W
Energization factor (in pulse / max.)	12
Energization (in pulse / max.)	24000 mA
Service voltage	No constant voltage!
Illuminated area	295 x 46 mm
Housing material	Aluminum (Black, Anodized)
Material	<ul style="list-style-type: none"> ■ Polyurethane (Cable) ■ PMMA, hardcoated (Protection optics)
Weight	1100 g
Risk group (DIN EN 62471)	Free group
Approvals	UL
Design	Barlight
Light source	LED
Color	red
Wavelength	625 nm
Deflection angle FWHM	30°



Technical data (typ.)	+20°C
Light intensity	<ul style="list-style-type: none"> ■ 100 kLx (100.0 mm / 100 %) ■ 310 kLx (100.0 mm / 400 %) ■ 515 kLx (100.0 mm / 800 %) ■ 62.0 kLx (200.0 mm / 100 %) ■ 178 kLx (200.0 mm / 400 %) ■ 324 kLx (200.0 mm / 800 %) ■ 24.0 kLx (500.0 mm / 100 %) ■ 66.0 kLx (500.0 mm / 400 %) ■ 115 kLx (500.0 mm / 800 %) ■ 7.50 kLx (1000.0 mm / 100 %) ■ 20.0 kLx (1000.0 mm / 400 %) ■ 38.0 kLx (1000.0 mm / 800 %)
Control	Flashable by means of flash controller
Shock/vibration load	30 g, 11 ms / 10 ... 55 Hz, 1.0 mm
Ambient temperature during operation	0 ... +40 °C
Protection type	IP 67
Connection	Cable, 2.5 m (flying leads, Use only with flash controller!)
More information / accessories	https://www.di-soric.com/208219