



209593
LI 104-12.5-1288-1340 I
Light grids

- With evaluation electronics LVE ... / LVX ... measuring and switching
- With evaluation electronics LVB ... switching
- Beam evaluation horizontal or diagonal
- Compact design
- Aluminum housing
- Easy to install



Function													
												CE	

Technical data (typ.)	+20°C, 24 V DC
Service voltage	20 ... 26 V DC (see evaluation electronics)
Assembly	Threaded bolt (3)
Profile cross section	12 x 24 mm
Dimension	<ul style="list-style-type: none"> ■ A: 70 mm ■ B: 600 mm ■ X: 13.5 mm ■ Y: 38.5 mm
Profile length	1340 mm
Housing material	Aluminum (natural)
Protection class	III, operation on protective low voltage
Evaluation	absolute, percentage, Configurable via evaluation electronics
Evaluation electronics	external
Output function	Configurable via evaluation electronics
Switching output	Configurable via evaluation electronics, NO, NC
Light source	LED
Color	Infrared
Wavelength	880 nm
Beam evaluation	via external evaluation electronics
Beam separation	12.5 mm



209593

LI 104-12.5-1288-1340 I

Light grids

Technical data (typ.)	+20°C, 24 V DC
Number of beams	104
Monitoring height	1288 mm
Range	250 ... 6000 mm (adjustable via evaluation electronics)
Measuring range	1288 mm
Ambient temperature during operation	-20 ... +40 °C
Protection type	IP 54 (IP 65 optional)
Connection	Cable, 4.0 m (with plug connector, additional variants on request)
More information / accessories	https://www.di-soric.com/209593