



209638
LI 96-10-950-1010 I
Light grids

- With evaluation electronics LVE ... / LVX ... measuring and switching
- With evaluation electronics LVB ... switching
- Beam evaluation horizontal or diagonal
- Compact design
- Aluminum housing
- Easy to install



Function													

Technical data (typ.)	+20°C, 24 V DC
Service voltage	20 ... 26 V DC (see evaluation electronics)
Assembly	Threaded bolt (3)
Profile cross section	12 x 24 mm
Dimension	<ul style="list-style-type: none"> ■ A: 105 mm ■ B: 400 mm ■ X: 13.5 mm ■ Y: 38.5 mm
Profile length	1010 mm
Housing material	Aluminum (natural)
Protection class	III, operation on protective low voltage
Evaluation	absolute, percentage, Configurable via evaluation electronics
Evaluation electronics	external
Output function	Configurable via evaluation electronics
Switching output	Configurable via evaluation electronics, NO, NC
Light source	LED
Color	Infrared
Wavelength	880 nm
Beam evaluation	via external evaluation electronics
Beam separation	10 mm

**209638****LI 96-10-950-1010 I****Light grids**

Technical data (typ.)	+20°C, 24 V DC
Number of beams	96
Monitoring height	950 mm
Range	250 ... 6000 mm (adjustable via evaluation electronics)
Measuring range	950 mm
Ambient temperature during operation	-20 ... +40 °C
Protection type	IP 54 (IP 65 optional)
Connection	Cable, 4.0 m (with plug connector, additional variants on request)
More information / accessories	https://www.di-soric.com/209638