




212924
BEK-P7-G5T-IBS
Spotlight

- Constant level of light intensity over the entire voltage range
- Homogeneous luminous field
- External trigger input
- Internal control of power output
- High efficiency
- Low levels of heat produced
- Robust metal housing



Function									



Technical data (typ.)	+20°C
Service voltage	18 ... 30 V DC
No-load current (max.)	145 mA (24 V DC)
Power	3.5 W (24 V)
Inverse polarity protection	Yes
Illuminated area	Ø 21 mm
Light aperture	axial
Housing material	Aluminum (Black, Anodized)
Material	PMMA, clear (Protection optics)
Weight	110 g
Protection class	III, operation on protective low voltage
Risk group (DIN EN 62471)	Risk group 2
Approvals	UL
Design	Spot light
Characteristics	Trigger input
Trigger input high level	> 3.4 ... 30.0 V
Trigger input low level	< 2.8 V
Light source	LED
Color	White
Wavelength	6500 K
Deflection angle FWHM	7°



212924
BEK-P7-G5T-IBS
Spotlight

Technical data (typ.)**+20°C**

Light intensity

- 25.0 kLx (500.0 mm)
- 6.00 kLx (1000.0 mm)
- 2.75 kLx (1500.0 mm)

Control

Integrated power control

Display

LED Green - Operation

Shock/vibration load

30 g, 11 ms / 10 ... 55 Hz, 1.0 mm

Ambient temperature during operation

0 ... +40 °C

Protection type

IP 67

Connection

Connector, M12, 3-pin

Connection cable

VK ...

More information / accessories<https://www.di-soric.com/212924>