



**213115**  
**SB-RGB-481-K-B5**  
**Signal lighting**

- Six segments: external trigger / segment mode / level mode / demo mode
- Easy operation is also possible without IO-Link
- Freely configurable functions via IO-Link
- Long life thanks to intelligent thermal management
- Large light field for optimal display of the machine status
- High protection type IP 67
- Magnetic holder set available as an option
- Adjustable mounting angle optionally available
- Pluggable diffusion filter optionally available



1) Illuminated area

Operating mode: External trigger

TRIG 1	TRIG 2	TRIG 3	Pre-Set	Factory setting	
				Var. 126	Var. 251-911
0	0	0	1	<input type="checkbox"/> Off	<input type="checkbox"/> Off
1	0	0	2	<input type="checkbox"/> Red	<input type="checkbox"/> Red
0	1	0	3	<input type="checkbox"/> Green	<input type="checkbox"/> Green
1	1	0	4	<input type="checkbox"/> Yellow	<input type="checkbox"/> Yellow
0	0	1	5	<input type="checkbox"/> Blue	<input type="checkbox"/> Blue
1	0	1	6	<input type="checkbox"/> Red	<input type="checkbox"/> Red
0	1	1	7	<input type="checkbox"/> Green	<input type="checkbox"/> Green
1	1	1	8	<input type="checkbox"/> Red Cycling	<input type="checkbox"/> Yellow

All Trigger Inputs have a delay ~50 ms.  
Pre-sets can be defined via IO-Link.

BK: black      BU: blue      WH: white  
 BN: brown      GY: grey

Function											

Technical data (typ.)	+20°C, 24 V DC
Service voltage	18 ... 30 V DC (Supply Class 2)
Internal power consumption	380 mA (24 V DC)
Power	9.1 W (24 V DC)
Inverse polarity protection	Yes
Illuminated area	440 x 30 mm
Housing length	480 mm
Housing height	10 mm
Housing width	40 mm
Housing material	Aluminum (natural, Anodized)
Material	PU, crystal clear (Window)
Weight	390 g
Protection class	III, operation on protective low voltage
Risk group (DIN EN 62471)	Free group
Approvals	UL
Model	Signal lighting
Product series	SB-RGB
Number of segments (max)	6
Operation modes	External trigger / segment mode / level mode / demo mode, LED operating modes: Static / Blinking / Flashing
Light intensity can be adjusted	10 to 100 %, via IO-Link
Trigger input high level	> 8.0 V
Trigger input low level	< 5.0 V
Trigger input	8 color presets: selectable via trigger 1 + 2 +3
Interface	<ul style="list-style-type: none"> <li>■ IO-Link (V1.1, COM2 38,4 kBd, 5000 µs)</li> <li>■ Process data</li> </ul>



**213115**  
**SB-RGB-481-K-B5**  
**Signal lighting**

<b>Technical data (typ.)</b>	<b>+20°C, 24 V DC</b>
Light source	LED
Color	Red, green, yellow, blue, white, orange, pink, user-defined (IO-Link)
Deflection angle FWHM	120°
Shock/vibration load	30 g, 11 ms / 10 ... 55 Hz, 1.0 mm
Ambient temperature during operation	0 ... +50 °C
Protection type	IP 67
Connection	Pigtail, 0.3 m, M12, 5-pin
Connection cable	VK ... /5
<b>More information / accessories</b>	<b><a href="https://www.di-soric.com/213115">https://www.di-soric.com/213115</a></b>