



**213754**  
**SBT-RGB-R50-4S-B5**  
**Signal column**

- Status display 360°
- Strong signal effect thanks to state-of-the art, high-efficiency LEDs
- Low energy consumption
- Can be used immediately thanks to three trigger inputs (eight predefined/user-defined color settings)
- Freely configurable functions via IO-Link (process data)
- Simple installation (M30 threading)



BN 1 ⊕  
 WH 2 Trigger 1  
 BK 4 ⊖ Trigger 3  
 BU 3 ⊖  
 GY 5 Trigger 2

**Legende / Legend:**  
 >RT< = Rot langsam blinkend / flashing red slowly  
 >>RT<< = Rot blitzend / rapidly flashing red  
 >BUZ< = Buzzer intermittierend / Buzzer intermittent (1Hz)  
 >>BUZ<< = Buzzer intermittierend / Buzzer intermittent (2.5Hz)

All Trigger Inputs have a delay ~50 ms.  
 Pre-sets can be defined via IO-Link.

TRIG 1	TRIG 2	TRIG 3	Pre-Set	Factory setting (Seg 1 / Seg 2 / Seg 3 / Seg 4 / BUZ)			
				Var. 4S		Var. 4B	
0	0	0	1	--	--	--	--
1	0	0	2	--	--	RT	--
0	1	0	3	--	GN	--	GN
1	1	0	4	--	YE	--	YE
0	0	1	5	BU	--	--	BU
1	0	1	6	WH	--	--	WH
0	1	1	7	--	--	>RT<	>BUZ<
1	1	1	8	--	--	>>RT<<	>>BUZ<<

BK: black      BU: blue      GY: grey      YE: yellow  
 BN: brown      GN: green      WH: white

Function										

Technical data (typ.)	+20°C, 24 V DC
Service voltage	18 ... 30 V DC (Supply Class 2)
Internal power consumption	230 mA (24 V DC)
Power	5.5 W (24 V)
Inverse polarity protection	Yes
Illuminated area	50 x 37 mm (Ø x H / segment)
Number of segments	4
Housing material	Aluminum (natural, Anodized)
Material	Polycarbonate (Diffusor)
Weight	310 g
Protection class	III
Approvals	UL
Model	Signal column
Operating modes	External trigger / segment mode / level mode / demo mode, LED operating modes: Static / Blinking / Flashing
Buzzer	Without buzzer
Color selection	Red, green, yellow, blue, white, orange, pink, user-defined
Light intensity can be adjusted	10 to 100 %, via IO-Link
Trigger input high level	> 8.0 V
Trigger input low level	< 5.0 V



**213754**

**SBT-RGB-R50-4S-B5**

**Signal column**

Technical data (typ.)	+20°C, 24 V DC
Trigger input	8 color presets: selectable via trigger 1 + 2 +3
Interface	■ IO-Link (V1.1, COM2 38,4 kBd, 5000 µs) ■ for parameterization (process data)
Color	RGB
Vibration load	10 ... 55 Hz / 0.35 mm
Ambient temperature during operation	0 ... +50 °C
Protection type	IP 65
Connection	Connector, M12, 5-pin
More information / accessories	<a href="https://www.di-soric.com/213754">https://www.di-soric.com/213754</a>