



213757
SBT-RGB-R50-5B-B5
Signal column

- Status display 360°
- Strong signal effect thanks to state-of-the art, high-efficiency LEDs
- Low energy consumption
- Can be used immediately thanks to three trigger inputs (eight predefined/user-defined color settings)
- Freely configurable functions via IO-Link (process data)
- Simple installation (M30 threading)
- Buzzer



Legende / Legend:

- >RT< = Rot langsam blinkend / flashing red slowly
- >>RT<< = Rot blitzend / rapidly flashing red
- >BUZ< = Buzzer intermittierend / Buzzer intermittent (1Hz)
- >>BUZ<< = Buzzer intermittierend / Buzzer intermittent (2,5Hz)

All Trigger Inputs have a delay ~50 ms.
Pre-sets can be defined via IO-Link.

TRIG 1	TRIG 2	TRIG 3	Pre-Set	Factory setting (Seg 1 / Seg 2 / Seg 3 / Seg 4 / BUZ)									
				Var. 5S				Var. 5B					
0	0	0	1	--	--	--	--	--	--	--	--	--	--
1	0	0	2	--	--	--	RT	--	--	--	--	RT	--
0	1	0	3	--	--	GN	--	--	--	GN	--	--	--
1	1	0	4	--	--	YE	--	--	--	YE	--	--	--
0	0	1	5	--	BU	--	--	--	--	BU	--	--	--
1	0	1	6	WH	--	--	--	--	--	WH	--	--	--
0	1	1	7	--	--	--	>RT<	--	--	--	>RT<	>BUZ<	>BUZ<
1	1	1	8	--	--	--	>>RT<<	--	--	--	>>RT<<	>>BUZ<<	>>BUZ<<

BK: black BU: blue GY: grey YE: yellow
 BN: brown GN: green WH: white

Function																

Technical data (typ.)		+20°C, 24 V DC
Service voltage		18 ... 30 V DC (Supply Class 2)
Internal power consumption		305 mA (24 V DC)
Power		7.3 W (24 V)
Inverse polarity protection		Yes
Illuminated area		50 x 37 mm (Ø x H / segment)
Number of segments		5
Housing material		Aluminum (natural, Anodized)
Material		Polycarbonate (Diffusor)
Weight		390 g
Protection class		III, operation on protective low voltage
Approvals		UL
Model		Signal column
Operating modes		External trigger / segment mode / level mode / demo mode, LED operating modes: Static / Blinking / Flashing
Buzzer		Yes, 80 (dB(A) typ. @ 50 cm)
Color selection		Red, green, yellow, blue, white, orange, pink, user-defined
Light intensity can be adjusted		10 to 100 %, via IO-Link
Trigger input high level		> 8.0 V
Trigger input low level		< 5.0 V

**213757****SBT-RGB-R50-5B-B5****Signal column**

Technical data (typ.)	+20°C, 24 V DC
Trigger input	8 color presets: selectable via trigger 1 + 2 +3
Interface	■ IO-Link (V1.1, COM2 38,4 kBd, 5000 µs) ■ for parameterization (process data)
Color	RGB
Vibration load	10 ... 55 Hz / 0.35 mm
Ambient temperature during operation	0 ... +50 °C
Protection type	IP 20
Connection	Connector, M12, 5-pin
Connection cable	VK ... /5-SB
More information / accessories	https://www.di-soric.com/213757