



213752
SBT-RGB-R50-3S-B5
Signal column

- Status display 360°
- Strong signal effect thanks to state-of-the art, high-efficiency LEDs
- Low energy consumption
- Can be used immediately thanks to three trigger inputs (eight predefined/user-defined color settings)
- Freely configurable functions via IO-Link (process data)
- Simple installation (M30 threading)



Legende / Legend:

- >RT< = Rot langsam blinkend / flashing red slowly
- >>RT<< = Rot blitzend / rapidly flashing red
- >BUZ< = Buzzer intermittierend / Buzzer intermittent (1Hz)
- >>BUZ<< = Buzzer intermittierend / Buzzer intermittent (2,5Hz)

All Trigger Inputs have a delay ~50 ms.
Pre-sets can be defined via IO-Link.

| TRIG 1 | TRIG 2 | TRIG 3 | Pre-Set | Factory setting (Seg 1 / Seg 2 / Seg 3 / BUZ) | | | | | |
|--------|--------|--------|---------|---|----|--------|---------|----|---------|
| | | | | Var. 3S | | | Var. 3B | | |
| 0 | 0 | 0 | 1 | -- | -- | -- | -- | -- | -- |
| 1 | 0 | 0 | 2 | -- | -- | RT | -- | -- | RT |
| 0 | 1 | 0 | 3 | GN | -- | -- | GN | -- | -- |
| 1 | 1 | 0 | 4 | -- | YE | -- | -- | YE | -- |
| 0 | 0 | 1 | 5 | BU | -- | -- | BU | -- | -- |
| 1 | 0 | 1 | 6 | WH | -- | -- | WH | -- | -- |
| 0 | 1 | 1 | 7 | -- | -- | >RT< | -- | -- | >BUZ< |
| 1 | 1 | 1 | 8 | -- | -- | >>RT<< | -- | -- | >>BUZ<< |

BK: black
BN: brown
BU: blue
GN: green
GY: grey
WH: white
YE: yellow

| Function | | | | | | | | | | |
|----------|--|--|--|--|--|--|--|--|--|--|
| | | | | | | | | | | |

| Technical data (typ.) | +20°C, 24 V DC |
|--------------------------------------|---|
| Service voltage | 18 ... 30 V DC (Supply Class 2) |
| Internal power consumption | 175 mA (24 V DC) |
| Power | 4.2 W (24 V) |
| Inverse polarity protection | Yes |
| Illuminated area | 50 x 37 mm (Ø x H / segment) |
| Dimensions of luminaire unit (Ø x H) | Ø 50.6 x 165 mm |
| Number of segments | 3 |
| Housing material | Aluminum (natural, Anodized) |
| Material | Polycarbonate (Diffusor) |
| Weight | 270 g |
| Protection class | III, operation on protective low voltage |
| Approvals | UL |
| Model | Signal column |
| Operating modes | External trigger / segment mode / level mode / demo mode, LED operating modes: Static / Blinking / Flashing |
| Color selection | Red, green, yellow, blue, white, orange, pink, user-defined |
| Light intensity can be adjusted | 10 to 100 %, via IO-Link |
| Trigger input high level | > 8.0 V |
| Trigger input low level | < 5.0 V |

**213752****SBT-RGB-R50-3S-B5****Signal column**

| Technical data (typ.) | +20°C, 24 V DC |
|--------------------------------------|---|
| Trigger input | 8 color presets: selectable via trigger 1 + 2 +3 |
| Interface | ■ IO-Link (V1.1, COM2 38,4 kBd, 5000 µs) ■ for parameterization (process data) |
| Color | RGB |
| Vibration load | 10 ... 55 Hz / 0.35 mm |
| Ambient temperature during operation | 0 ... +50 °C |
| Protection type | IP 65 |
| Connection | Connector, M12, 5-pin |
| Connection cable | VK ... /5-SB |
| More information / accessories | https://www.di-soric.com/213752 |